

# FMSL 3 D Centrifugal Disc Finisher

## Features

- Highly wear resistant hot-poured urethane insert
- Optimized disk geometry for ideal rotation
- Digital timer for easy time adjustment
- Specially developed gap technique
- Low heat generation
- Includes media starter kit
- Compact and lightweight
- 110/220V Single Phase



### Benchtop Model Complete with Bowl

The latest development in our popular SL product range is specifically designed for the smallest batches.

A high polished finished can be obtained with the proper combination of cut down (grinding) and polishing media's.

The gap system allows the processing of parts with thicknesses of as little as .012 and hollow parts with wall thickness as little as .003 can be gently deburred or polished.

The heavy-duty urethane bowl simply twist's off and can be swapped emptied easily. An optional dry bowl can be purchased allowing both wet and dry processing in one easy to use, low cost machine!

Optional accessories include a dosing pump with container, bowl cover, and a sturdy aluminum extrusion table/frame system. Digital process timer is standard.

TECHNICAL DATA					
Machine Type	Height (mm)	Width (mm)	Depth (mm)	Volume (L)	Weight (kg)
SL 3W	360	320	260	3	10

**Distributed By:**

**Bel Air Finishing Supply**  
110 Byfield St.  
Warwick, RI 02888  
**Phone:** 401.781.4407  
**Fax:** 401.781.4498  
**E-mail:**  
belairfinishing@msn.com